

Wall Mounted Concealed Fitting

Product Type

Wall Mounted Concealed Fitting

Features & Specifications

- 5 3/4" Cast Spout with Pail Hook and Wall Brace
- 3/4" Male Hose Thread Outlet
- 3" Metal Cross Handles with Secured Red and Blue Service Buttons
- Slow Compression Operating Cartridges
- Elevated Atmospheric Vacuum Breaker with "G" 3/8" Offset Adjustable Supply Arms with 1/2" NPT Female Thread Inlet
- Integral Service Stops
- Tear Drop Wall Escutcheons

Performance Specification

- Rating Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Compliant To

- ASME A112.18.1M
- CSA B125.1
- NSF 61, Section 9

Job Name \_\_\_\_\_

Item Number \_\_\_\_\_

Section/Tag \_\_\_\_\_

Model Specified \_\_\_\_\_

Architect \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor \_\_\_\_\_

☐ Submitted as Shown


☐ Submitted with Variations

Date \_\_\_\_\_



### Architect/Engineer Specification

Chicago Faucets No. 911-ISCP, polished chrome plated solid cast brass construction. Elevated vacuum breaker, 5-3/4" spout with pail hook, wall brace and 3/4" male garden hose thread outlet. Cross metal handles with tear drop escutcheons, eight-point tapered broach and secured, color-coded index buttons. Slow compression renewable cartridge that closes with water pressure, with square tapered broach feature to help facilitate handle removal. 8" rigid valve body centers with 1/2" NPT female union nut supply inlets. Integral supply stops in body for servicing cartridges. Mounting hardware included. This product is tested and certified to ASME A112.18.1 and CSA B125 industry standards.



### Operation and Maintenance

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning the product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at [www.chicagofaucets.com](http://www.chicagofaucets.com).

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.

