

# ACCESSORIES AND PARTS

## 99TF



### Product Type

Triple Force™ Low-Flow Pre-Rinse Valve

### Features & Specifications

- Water Conserving Pre-Rinse Spray Valve
- 0.91 / 0.99 GPM @ 60 PSI
- Stainless Steel Nozzle Body
- Rotating Rubber Nose Cone
- Three Stainless Steel Tips for Choice of Three Spray Patterns: 15-degree Fan Spray (0.99 gpm @ 60 PS
- 3/4" - 14 UNS Male Thread Inlet
- Compatible with Fisher and T&S Hoses

### Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA

Job Name \_\_\_\_\_

Item Number \_\_\_\_\_

Section/Tag \_\_\_\_\_

Model Specified \_\_\_\_\_

Architect \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor \_\_\_\_\_

Submitted as Shown       Submitted with Variations


Date \_\_\_\_\_



2100 South Clearwater Drive  
Des Plaines, IL  
P: 847/803-5000  
F: 847/803-5454  
Technical: 800/TEC-TRUE  
www.chicagofaucets.com

**Architect/Engineer Specification**

Chicago Faucets No. 99TF polished chrome plated solid brass construction. Integral inlet shank(s). Water conserving pre-rinse spray valve. 0.91 / 0.99 GPM @ 60 psi. Stainless steel nozzle body. Rotating rubber nose cone. Three stainless steel tips for choice of three spray patterns: 15-degree fan spray (0.99 GPM @ 60 ps. 3/4" - 14 UNS male thread inlet. Compatible with fisher and t&s hoses. Mounting hardware included. This product is tested and certified to industry standards: ASME A112.18.1/CSA B125.1, and Certified to NSF/ANSI 61, Section 9 by CSA.



**Operation and Maintenance**

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning the product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at [www.chicagofaucets.com](http://www.chicagofaucets.com).

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.



2100 South Clearwater Drive  
Des Plaines, IL  
P: 847/803-5000  
F: 847/803-5454  
Technical: 800/TEC-TRUE  
[www.chicagofaucets.com](http://www.chicagofaucets.com)