



model 7601.10.2  
Portable Units

## FEATURES & BENEFITS

### CONSTRUCTION

Stainless steel constructed tank makes for a solid portable unit with added resistance against corrosion and breakage.

### FLOW CONTROLS

Green ABS plastic Soft-Flo anti-surge heads head equipped with portable unit distributes water at .25 gpm (2) when pressure is between 30 and 90 psi to provide a thorough irrigation process.

### VALVES

Eyewash valve comes equipped with stainless steel ball and stem for added protection against corrosion and breakage. Unit also comes with a chrome-plated brass squeeze valve supplied with a 6.25 gpm flow control.

### ADDED PROTECTION

Green polyethylene plastic dust covers that release with water pressure keep the unit protected from debris up until the last second before use further optimizing operation. The 6' hose extends the portable units reach and is pressure rated at 250 psi making for a better piece of emergency equipment.

### SAFETY

Air pressure gauge, pressure relief valve, tire-type air fill valve, and supplied bottle of bacteriostatic additive decrease the possibility of mishaps and make for a safer piece of emergency equipment.

## OPTIONS

- Cart: Model 9007 cart designed to transport all 10 through 15 gallon portable eyewashes, 7500 or 7501 series, and 9009 wastewater container. Unit is constructed of heavy-duty 1" tubular frame with green powder-coated finish and comes equipped with four solid rubber wheels.
- Bacteriostatic Additive: Model 9082, bacteriostatic preservative for use in portable eyewash stations. One 8 oz. (237 ml) bottle will preserve 6 to 20 gallons of portable water for up to six months. Four bottles per carton.

To see all options for this model, visit [www.hawesco.com](http://www.hawesco.com)



## SPECIFICATIONS

Model 7601.10.2 portable air pressure operated eyewash with body spray shall include a stainless steel 13-gallon ASME 165 psi rated tank, ABS plastic anti-surge eyewash heads with .25 gpm (2) flow controls and dust covers, chrome-plated brass ball valve equipped with stainless steel ball and stem, 160 psi air pressure gauge, 110 psi air pressure relief valve, and tire-type air fill valve. Unit shall also include squeeze-valve operated body spray with green ABS plastic spray head, label-mounted operating instructions, and 1 bottle of bacteriostatic additive to permit storage of water for six months.

## APPLICATIONS

Where the eyes of any person may be exposed to injurious or corrosive materials, when suitable facilities for quick flushing of the eyes needs to be provided and a continuous supply of water is not available. Although the 7601.10.2 may be used in a wide variety of locations, it is ideal for the remote and low traffic areas where protective and mobile measures may still be needed. Emergency eyewash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7601.10.2 is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.