

FEATURES & BENEFITS

SAFETY

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

VALVE

Units pull-down to activate design produces a full continuous flow of water and provides an easy start to the irrigation process.

MOUNTING

Unit mounts at the back of sink so when the unit is not in use, it is as far out of the way as possible.

EYE/FACE WASH

AXION MSR™ eye/face wash head (patent pending) uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

ANTIMICROBIALLY TREATED

AXION MSR™ eye/face head is antimicrobially treated using the natural protection of silver. Impregnating these components with silver helps protect the head against the growth of mold and mildew on the treated components. AXION MSR™ is the only eye/face product on the market to feature antimicrobial protection.

OPTIONS

- ❑ Tempered Water Blending Systems: Model TWBS.EW, prepackaged, fully engineered and tested hot and cold water blending system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat.# 5,350,112).
- ❑ Tempered Water Blending Valves: Model 9201, thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- ❑ Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" double pole, double throw flow switch.
- ❑ Tempered Water Blending Valves: Model 9201EF, thermostatic mixing valve that mixes hot and cold water to supply tempered water to eyewashes requiring flow up to 7 gpm @ 30 psi.

To see all options for this model, visit www.hawsc.com



SPECIFICATIONS

Model 7610 barrier-free sink/countertop eye/face wash shall include an antimicrobially treated AXION MSR™ eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral 3.7 gpm flow control. polished chrome brass single action pull-down valve body, wheel chair accessibility, universal sign, and 1/2" O.D. slip joint inlet.

APPLICATIONS

Where safety is of the utmost importance and the eyes of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing and cleansing of the eyes must be provided within the work area for immediate emergency use. When installed properly, the stable construction, counter top design of the 7610 is space efficient with its rear mounting location, and can accommodate barrier-free access.

Model is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.