



# model 8111FP

Drench Showers

## FEATURES & BENEFITS

### VALVES

Valve is designed so the full flow of fluid remains on with a simple push of a stainless steel flag. Unit also comes equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage. Self-draining valve assembly is designed for installation behind the mounting wall with a maximum wall thickness of 15", in a non-freezing environment, so the unit maintains full emergency capability in freezing conditions.

### QUALITY CONTROL

Valve assembly is pre-built for reduced installation time and an added peace of mind for the installer.

### SAFETY

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

### SHOWER HEAD

AXION MSR™ ABS plastic drench shower head uses a hydrodynamic design to give equal distribution of water throughout the entire footprint of flow.

## OPTIONS

- Alarm: Model 9001, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a double pole, double throw flow switch.
- Tempered Water Blending Systems: Model TWBS.SH, prepackaged, fully engineered and tested system for mixing hot and cold water to provide tempered water up to 40 gpm for emergency showers and eyewashes (Pat.# 5,350,112).
- Tempered Water Blending Valves: Model 9202, thermostatic mixing valve that mixes hot and cold water for the tempering of shower units at a maximum flow rate of 40 gpm.
- Shower Head: Model 8127FC, corrosion-resistant 10-1/2" stainless steel showerhead with integral 20 gpm flow control.

To see all options for this model, visit [www.hawsc.com](http://www.hawsc.com)



## SPECIFICATIONS

Model 8111FP freeze-resistant drench shower shall also include the AXION MSR™ hydrodynamic designed ABS plastic shower head with 20 gpm flow control, and brass stay-open ball valve equipped with stem and stem extension for 15" max wall thickness. Unit shall also include a stainless steel push flag, universal sign, and 1" IPS supply.

## APPLICATIONS

Where the body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching and cleansing of the body shall be provided within the work area for immediate emergency use. Emergency deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8111FP is certified by CSA & IAPMO to meet the ANSI Z358.1-2004 Standard for Emergency Eyewash and Shower Equipment.