

FEATURES & BENEFITS

SAFETY

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

EYE/FACE WASH VALVE

Valve is designed so full continuous flow occurs with the simple squeeze of a lever providing an easy start to the irrigation process.

HOSE

The 12' recoil swivel hose delivers an extended coverage area and is pressure rated at 200 psi to optimize durability.

MOUNTING

Wall-mounted design with wall hook allows for easy locating as well as a space efficient piece of emergency equipment.

EYE/FACE WASH

AXION MSR® eye/face wash head (patent pending) uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

ANTIMICROBIALLY TREATED

AXION MSR® eye/face head is antimicrobially treated using the natural protection of silver. Impregnating these components with silver helps protect the head against the growth of mold and mildew on the treated components. AXION MSR® is the only eye/face product on the market to feature antimicrobial protection.

OPTIONS

- Vacuum Breaker: Model SP212 is a chrome-plated brass vacuum breaker.
- Repair Kit: Model VRKSP248 valve repair kit for Model SP248 squeeze handle valve.
- Tempered Water Blending Valves: Model 9201, thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" double pole, double throw flow switch.

To see all options for this model, visit www.hawscow.com



SPECIFICATIONS

Model 8905 wall mounted eye/face wash and body spray shall include an antimicrobially treated AXION MSR™ eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral 3.7 gpm flow control, chrome plated brass stay-open squeeze lever valve, 12-foot yellow recoil hose with chrome-plated swivel fitting at one end, universal sign, and 1/2" IPS inlet. In order to comply with state codes the use of a vacuum breaker is required with all hand held eye/face wash body spray units (Haws offers model SP212)

APPLICATIONS

Perfect for the environment where safety is of the utmost importance and an extended coverage area may be needed. When installed properly, the functional constructed, wall mounted design of the 8905 is not only space efficient it meets the current ANSI standards of the Federal State Drinking Water Act.

Unit 8905 is certified by CSA & IAPMO to meet the ANSI Z358.1-2004 Standard for Emergency Eyewash and Shower Equipment.