SPEAKMAN®

SE-601

SAFE-T-ZONE® EMERGENCY SHOWER AND EYE/FACE WASH

DESCRIPTION

Floor mounted emergency deluge shower and aerated eye/face wash combination unit. Shower is supplied with a 1" NPTF self-closing valve, activated by a pull chain and ring. Eye/face wash is supplied with 1/2" NPTF stay-open full flow ball valve, activated by push handle.

SPECIFICATIONS

Showerhead: 8" dia. cycolac® yellow plastic. **Flow control:** Internal 20 gpm regulator. **Valve:** 1" NPT female brass, chrome-plated.

Self-closing valve.

Activator: 8" dia. stainless steel ring.

Stanchion: 1-1/4" IPS steel piping with brass fittings.

Inlet & waste: 1-1/4" NPT female.

Floor flange: Brass casting with (3) 17/32" dia.

mounting holes on 9" dia. bolt circle, spaced 120° apart.

Finish: DuraJadeTM

EYE/FACE WASH

Bowl: 300 series stainless steel

Spray Heads: (6) brass, chrome-plated aerated **Valve:** ½" NPT female brass, chrome-plated **Activator:** Stainless steel push handle

Shrouds: Yellow Polypropylene

Inlet: 1/2" NPT female

Strainer: Brass, chrome-plated, in-line **Performance:** 3.0 gpm @ 30 psi **Compliance:** ANSI Z358.1

Universal Emergency Sign Included

OPTIONS

⅃ HFO	Hand foot operation
☐ FPV	Freeze protection valve
☐ SPV	Scald protection valve
☐ FLW	Flow switch
□HS	Hand held spray
\square TS	Top supply
□ SSH	Stainless steel showerhead
☐ SSBV	Stainless steel ball valves
□ ВН	Chrome plated brass showerhead

7 3/4" (197mm)	(610mm)		
Ŷ.			
		1 1/4" NPTF	
71.00	69" MAX FROM FLOOR		
7'-0" TO FLOOR (2134mm)	(1753mm)		
		5'-5"	
	44" (1118mm)	(1651mm)	
		1-1/4" NP WASTE	11
1			
		6" (152mm)	

Job Name		
Location		
Architect/Engineer		
Sales Representative		
Wholesaler		
Date	Model #	