

T&S BRASS AND BRONZE WORKS, INC.

2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690



Model No.

EC-3103-TMV

Item No. REG. #A2601

ITEM		
NO.	SALES NO.	DESCRIPTION
1	016355-45	Aerator W/ Key, Vandal Resistant, 2.2 GPM, 13/16-27 male
2	017195-45	Angled Sensor w/ Cable
3	016297-45	Inlet Hose, Faucet, 1/2" NPSM-F x 1/4" NPSM-F
4		ChekPoint Electronic Module (Blue)
	EC-FILTER	Replacement Filter
6	5EF-0002	A/C Transformer
7	016061-25	Adapter 9/16-24UN Female x 1/2-14NPSM Male Chrome Plated
8	EC-TMV	ASSE 1070 Thermostatic Mixing Valve
9	5EF-0005	Supply Hose, 9/16-24 Female x 1/2" NPSM
10	Q015425-45	Vandal Resistant Key
5 7 8 8 Available Wat	er Flow Contr	Label for Flow Control Switch Settings is located on Inside of Back Cover. Flow Control Switches are located inside Module Housing in Black Box next to Battery Compartment. *Switches are set to DEFAULT position: Auto Time Out = 10 seconds Shut Off Delay = 1 second Remove (4) screws and back cover to access switches.
	NO. 1 2 3 4 5 6 7 8 9 10	NO. SALES NO. 1 016355-45 2 017195-45 3 016297-45 4 016647-45 5 EC-FILTER 6 5EF-0002 7 016061-25 8 EC-TMV 9 5EF-0005 10 Q015425-45

(6) Auto Time Out Selections - 10 sec, 25 sec, 45 sec, 60 sec, 3 min, 20 min

(4) Shut Off Delay Selections - 1 sec, 2 sec, 4 sec, 5 sec, 6 sec

Product Specifications: Chrome Plated Brass Electronic Faucet: 4" c/c Drawn Approved Checked Deck Mount Spout w/ VR Aerator, AC/DC Control Module w/ DHL DMH JHB Internal Flow Control Setting Switches, Thermostatic Temperature Control Mixing Valve w/ Integral Check Valves, 18" Long Hot & Cold Supply Stop Flexible Connector Hoses Scale: Date: NTS 10/16/09

Sheet: 2 of 2