



model 7656WC

Barrier-Free Emergency Equipment

FEATURES & BENEFITS

CONSTRUCTION

Type 304 Stainless Steel recessed pull down cabinet design provides a space efficient full functioning piece of emergency equipment in the time of an emergency.

FLOW CONTROLS

Green ABS Feather-Flo heads equipped with built-in 2.5 gpm (2) self-regulating flow controls provide multiple soft-and-steady flowing streams of water for a maximum coverage area. Further equipped with front cover/drain pan, unit stays protected from debris up until the last second before use.

VALVE

Valve is designed to make the flushing of fluid occur with the pull of a lever.

ADDED PROTECTION

Stainless steel drain pan collects eye/face wash waste within the cabinet so the cleansing area remains as clean as possible throughout the irrigation process. Barrier-free pull-down design accommodates all users including wheel chair accessibility.

QUALITY CONTROL

The entire unit is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind.

SAFETY

Barrier-free design, 8" x 10-3/4" universal emergency sign, and a test card to record weekly testing of emergency equipment bring safety to a whole new level.



SPECIFICATIONS

Model 7656WC barrier-free eye/face wash shall include a fully recessed wall mounted stainless steel cabinet with drain pan, green ABS plastic eye/face wash heads with integral flow controls and dust covers, wheel chair accessibility, polished chrome-plated brass pull-down valve, and brass stay-open supply ball valve equipped with stainless steel ball and stem. Unit shall also include front-access maintenance panel, universal sign, 1/2" IPS inlet, and 1-1/2" IPS waste.

APPLICATIONS

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing of the eyes and face shall be provided within the work area for immediate emergency use. This unit brings a nice finish to any location, all while offering a wide coverage area for the face and eyes. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7656WC is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.

OPTIONS

- ❑ Tempered Water Blending Systems: Model TWBS.EW, prepackaged, fully engineered and tested hot and cold water blending system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat.# 5,350,112).
- ❑ Tempered Water Blending Valves: Model 9201, thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- ❑ Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" double pole, double throw flow switch.
- ❑ Tempered Water Blending Valves: Model 9201EF, thermostatic mixing valve that mixes hot and cold water to supply tempered water to eyewashes requiring flow up to 7 gpm @ 30 psi.

To see all options for this model, visit www.hawesco.com