



model 7752WC

Barrier-Free Emergency Equipment

FEATURES & BENEFITS

QUALITY CONTROL

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time.

SAFETY

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

CONSTRUCTION

18 gauge Type 304 Stainless Steel, No. 4 satin finish receptor incorporates a space efficient and durable design that extends a full 19" from the wall to provide barrier-free accessibility.

VALVE

Valve is designed to make the flushing of fluid occur with the push of a stainless steel flag, and is equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

EYE/FACE WASH

AXION MSR[®] eye/face wash head (patent pending) uses an inverted directional laminar flow to sweep contaminants away from the vulnerable nasal cavity.

ANTIMICROBIAL TREATED

AXION MSR[®] eye/face head is antimicrobially treated using the natural protection of silver. Impregnating these components with silver helps protect the head against the growth of mold and mildew on the treated components. AXION MSR[®] is the only eye/face product on the market to feature antimicrobial protection.



SPECIFICATIONS

Model 7752WC wall mounted barrier-free eye/face wash shall include a stainless steel bracket with a integral stainless steel 11" round bowl, an antimicrobially treated AXION MSR[™] eye/face wash head to help protect against the growth of mold and mildew on the treated components, and shall feature inverted directional laminar flow which achieves zero vertical velocity supplied by an integral 3.7 gpm flow control, wheel chair accessibility, brass stay-open ball valve with stainless steel ball and stem, brass 1-1/4" waste trap, universal sign, and 1/2" IPS inlet.

OPTIONS

- ❑ Eyewash Head Assembly: Model SP60 chrome-plated brass eyewash head assembly with SP10 Soft-Flo polished chrome-plated brass anti-surge eyewash heads, and 9095 dust covers. 1/4" IPS.
- ❑ Tempered Water Blending Systems: Model TWBS.EW, prepackaged, fully engineered and tested hot and cold water blending system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat.# 5,350,112).
- ❑ Tempered Water Blending Valves: Model 9201, thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- ❑ Eyewash Head Assembly: Model SP62FC with Soft-Flo SP11FC ABS plastic eyewash anti-surge heads, one-piece electropolished Type 304 stainless steel eyewash yoke, and 9095 dust covers. 1/4" IPS.

To see all options for this model, visit www.hawsc.com

APPLICATIONS

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing of the eyes and face shall be provided within the work area for immediate emergency use. This unit brings a nice finish to any location, all while offering a wide coverage area for the face and eyes. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7752WC is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.