



model **8330**
Combination Units

FEATURES & BENEFITS

CONSTRUCTION

1-1/4" Type 304 Stainless Steel pipe and fittings along with cast finished stainless steel 9" diameter floor flange provide a superior defense in a highly corrosive environment.

FLOW CONTROLS

Corrosion resistant stainless steel showerhead comes equipped with an integral 20 gpm flow control, with the Soft-Flo eye/face wash heads and 16 spray opening electro-polished face ring equipped with built in 1.2 gpm (2) and 1.8 gpm flow controls allowing all parts of the equipment to be safely used simultaneously.

VALVES

Eye/face wash valve is designed to make the flushing of fluid remains occur with the simple push of a stainless steel flag. Shower ball valve is designed to make the flushing of fluid remains occur with the pull of a triangular lever.

STRAINERS/FILTERS

Type 304 Stainless Steel in-line 50 x 50 mesh water strainer supplies added protection against corrosion and prevents debris from reaching the eye/face wash so the 8330 stays functioning at its best. Strainer is easily serviceable. Stainless steel dust cover protects eye/face wash and spray ring as well as bowl up until the last second before use further optimizing operation.

QUALITY CONTROL

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time.

BOWL

The 11" round stainless steel receptor is supplied with a No. 2L bright finish on its exterior, and a satin finish inside.



SPECIFICATIONS

Model 8330 all stainless steel combination shower and eye/face wash shall include a stainless steel 10-1/2" shower head with integral self-regulating 20 gpm flow control, stainless steel 11" round bowl, stainless steel Soft-Flo anti-surge eyewash heads and face ring, stainless steel dust cover, stainless steel 50 x 50 mesh water strainer, and stainless steel stay-open shower and eyewash ball valves equipped with stainless steel ball and stem. Unit shall also include a stainless steel cast 9" diameter floor flange, Type 304 Stainless Steel pipe and fittings, universal sign, self-adhesive high visibility Safety Green and bright yellow stripes, and 1-1/4" IPS supply.

OPTIONS

- Alarm: Model 9001, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a double pole, double throw flow switch.
- Shower Test Kit: Model 9010 shower test kit includes holding rod, upper corrosion-resistant ring to encircle the shower head, and Tyvek waterproof tunnel shaped tube to guide the water column to container or drain.
- Universal Sign: Model 9020 green and yellow ABS plastic 3-sided high visibility sign.
- Privacy Curtain: Model 9037, privacy curtain designed to be used on horizontal emergency drench shower or combination emergency drench shower and eyewash units.

To see all options for this model, visit www.hawasco.com

APPLICATIONS

In an environment where materials need to withstand the greatest corrosion, where eyes, face, or body of any person may be exposed to these injurious or corrosive materials, suitable facilities for quick drenching or flushing of the eyes, face, and body shall be provided within the work area for immediate emergency use. Emergency eye/face wash facilities and deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8330 is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.