



## FEATURES & BENEFITS

### CONSTRUCTION

Stainless steel recessed pull down cabinet design provides a space efficient full functioning piece of emergency equipment in the time of an emergency.

### FLOW CONTROLS

Stainless steel showerhead and Omni-Flo wrap-around eye/face wash equipped with integral 20 gpm flow shower control and built-in 7 gpm flow eye/face control allow both parts of the equipment to be safely used simultaneously. Flow controls provide the optimal water flow for a superior coverage area.

### VALVES

Eye/face wash and shower ball valves are designed to make the flushing of fluid occur with the pull down of the recessed cabinet and pull down lever, and come equipped with a stainless steel ball and stem to provide protection against corrosion and breakage.

### FLUSH MOUNT

Space efficient wall flush-mount design with pull down lever allow for a barrier-free design. Stainless steel drain pan collects eye/face wash waste within the cabinet so the cleansing area remains as clean as possible throughout the irrigation process.

### QUALITY CONTROL

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time.



## OPTIONS

- ❑ Alarm: Model 9001, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a double pole, double throw flow switch.
- ❑ Discontinued Emergency Equipment: Model 9001.220V 220 VAC emergency alarm and light system. Buzzer and flashing light are activated by flow switch when emergency shower or eyewash is in use.
- ❑ Alarm: Model 9001EXP 120 VAC Class 1, Division 2, Groups B, C, and D emergency alarm system. Buzzer and flashing light are activated by an 1-1/4" double pole, double throw flow switch.
- ❑ Shower Test Kit: Model 9010 shower test kit includes holding rod, upper corrosion-resistant ring to encircle the shower head, and Tyvek waterproof tunnel shaped tube to guide the water column to container or drain.

To see all options for this model, visit [www.hawesco.com](http://www.hawesco.com)

## SPECIFICATIONS

Model 8356WC barrier-free recessed wall-mounted combination shower and eye/face wash shall include a stainless steel 10-1/2" showerhead with integral self-regulating 20 gpm flow control, ABS plastic Omni-Flow wrap around eye/face wash, wheel chair accessibility, fully recessed stainless steel cabinet, shower handle operated brass stay-open ball valve equipped with stainless steel ball and stem, pull-down eye/face wash activation with drain pan, universal sign, 1" IPS supply, and 1-1/2" IPS waste.

## APPLICATIONS

Where the eyes, face, or body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching or flushing of the eyes, face, and body shall be provided within the work area for immediate emergency use. Emergency eye/face wash facilities and deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8356WC is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.