

FEATURES & BENEFITS

AUDIBLE/VISUAL

Notification of an emergency is clearly noticeable with a brightly flashing amber light, and easily recognizable with a 90 db buzzer. Buzzer can be silenced during testing by merely putting your thumb over it. The buzzer will go silent and once the test is done, will reset itself.

FLEXIBILITY

The alarm is easily placed in a number of mounting configurations with the supplied pipe clamp.

FLOW SWITCH

The alarm is activated by an 1-1/4" double pole, double throw brass flow switch that is supplied with an extra set of electrical contacts for remote alarm hook-up.



OPTIONS

- ❑ Alarm: Model 9001EXP 120 VAC Class 1, Division 2, Groups B, C, and D emergency alarm system. Buzzer and flashing light are activated by an 1-1/4" double pole, double throw flow switch.
- ❑ Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" double pole, double throw flow switch.

To see all options for this model, visit www.hawesco.com

SPECIFICATIONS

Model 9001 emergency alarm and light system will be operated by a double pole, double throw flow switch, which contains multiple sets of contacts for remote activation, and activates an amber flashing light and buzzer at 90 db, audible at 10 feet (buzzer can be silenced during testing). System can be mounted to pipe or wall. Voltage: 120 VAC, 50 or 60 cycles. Supply: 1-1/4" IPS. Model 9001 is CSA electrical certified, TYPE 4.

APPLICATIONS

Specifically, this alarm can be used with almost any Haws combination shower/eyewash model.