



Water Coolers



SEMI-RECESSED

PLF8S, PLF14S

Models

PLF8S delivers 8 gph of chilled drinking water.
PLF14S delivers 14 gph of chilled drinking water.

Standard Features

- > Waterways Are Lead-Free In Materials & Construction
- > Dial-A-Drink® Bubbler
- > Stainless Steel Top
- > Welded, Heavy-Gauge Steel Frame
- > High-Efficiency Cooling Tank and Coil
- > Refrigerant R-134a
- > Product Certified to NSF/ANSI Standard 61, Annex G (AB1953)
- > Limited 5-year Warranty

Finishes

- > Standard Cabinet Finish: Sandstone Powder Coat
- > Optional finishes at no extra cost: Graystone Powder Coat
- > Optional finishes at extra cost: Stainless Steel, Regency Bronze

Accessories

- > Carafe/Glass Fillers (Factory Installed)
- > PLF8S/PLF14S (030239-002)



Components in these water coolers are lead free as defined by the Safe Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Installation

- > Prior to roughing-in consult with local, state, and federal codes
- > Shipped with complete instructions
- > Removable panels provide easy access for installation

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty: One year on sealed refrigeration system and most components parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Product Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of $\leq 0.25\%$) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953).

Models covered by these specifications comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian Safety Standards.



| Model | 50° F Drinking Water 90° F Ambient Air Temp* | | | Hot 'N Cold™ Model | 115 Volts, 60 HZ | | | Glass Filler Acc. Option | Cabinet Color Finish | Net Wt. Approx. |
|--------|-------------------------------------------------|------------------|------------|-----------------------|------------------|-------------------|----------------|-----------------------------|-------------------------|--------------------|
| | Rated Capacity GPH | Base Rate GPH | Pre-Cooler | | Compr. HP | Full Load Amps | Rated Watts | | | |
| PLF8S | 8.0 | 8.0 | No | No | 1/5 | 4.6 | 390 | Yes | Yes | 71 Lbs. |
| PLF14S | 14.0 | 8.0 | Yes | No | 1/5 | 4.6 | 390 | Yes | Yes | 77 Lbs. |

*Industry Standard Rating Condition 80° F inlet water temperature.

Specifications subject to change without notice

