



Water Coolers



BARRIER-FREE FROST-RESISTANT MODULAR

M110FZ

Suggested Specification

Model M110FZ is a non-refrigerated, frost-resistant drinking fountain. Fountain is activated by a push button and shall be designed to eliminate splashing and standing water. Bubbler shall have flexible bubbler guard and operate between 20 and 120 PSI. A plumbing box containing an air operated valve and drain system shall be included for remote mounting in a heated area. A wall panel and mounting bracket shall be included with the fountain. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards. This unit shall comply with the Safe Drinking Water Act and Lead Contamination Control Act.

Model

M110FZ is a distinctive, space saving, frost-resistant fountain that serves the disabled as well as the able-bodied. It can be installed with the M140FZ to provide split level combination.

Standard Features

- > Waterways are Lead-Free in Materials & Construction
- > Stainless Steel Surfaces
- > Stainless Steel Wall Surfaces
- > Heavy duty galvanized steel wall mounting bracket
- > Air-Operated Valve mounted in plumbing box to be located in heated area inside wall.
- > Air valve and drain components mounted on heavy gauge plate, furnished with full cover
- > Product Certified to NSF/ANSI Standard 61, Annex G (AB1953)
- > Limited 1-Year Warranty

Finishes

- > Standard Finish: Stainless Steel

Installation

- > Prior to roughing-in, consult local, state and federal codes for proper mounting heights and wall mounting plate
- > Shipped with complete instructions and wall mounting bracket
- > Prior to roughing-in, review factory mounting and installation procedures
- > Mounting template available



Components in this cooler are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

Limited 1-Year Warranty (Continental limits of the United States and Canada): One year from date of installation on parts only. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Export Warranty: One year on component parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Product Certified to NSF/ANSI Standard 61, Annex G (weighted average lead content of <=0.25%) and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953).

Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters' Laboratories to U.S. and Canadian standards and European Union Directives.



Certified to
NSF/ANSI 61-G

Physical Dimensions In Inches						
Model	Style	Height	Width	Depth	Extended From Wall	Net Weight Approx.
M110FZ	Modular Frost Resistant	6 1/8"	13 1/8"	16 1/8"	16 1/8"	43 lbs

OASIS™ FROST RESISTANT MODULAR DRINKING FOUNTAIN MODEL M110FZ

