SPEAKMAN®

SE-555 EYESAVER® EYE WASH

DESCRIPTION

SE-555 Eyesaver pedestal mounted freeze protected eyewash offers twin aerated sprays for gentle yet thorough rinsing of the eyes. The unit features a rectangular stainless steel bowl and paddle handle activation. Supply activated by frost-proof hydrant.

SPECIFICATIONS

BOWL: 300 Series Stainless Steel.

SPRAY HEADS: (2) Aerated Yellow Nylon Spray

Outlets.

FROST PROOF VALVE: 1" NPT Female Brass.

STANDARD VALVE BURY DEPTH: 42".

ACTIVATOR: Push Handle. INLET: 1" NPT Female.

PIPE: 1-1/4" IPS Galvanized Steel.

WASTE: 1-1/4" NPT Female.

FINISH: Safety Green Paint.

Universal Emergency Sign Included Compliance: Meets ANSI Z358.1-1998

(330mm) **FLOOR** 42" TO LINE FL00R (1067mm) 42" BURY DEPTH STANDARD (1067mm) OTHER DEPTHS CONCRETE AVAILABLE AS **FOOTING** SPECIAL ORDER TO SUIT FROST CONDIDITIONS IN LOCALITY NOT LESS THAN THREE (3) CUBIC FEET OF CRUSHED STONE AROUND AND BELOW WASTE OUTLET FOR DRAINAGE 1" NPTF INLET

OPTIONS

☐ Flow Switch (FLW)

Job Name		
Location		
Architect/Engineer		
Sales Representative _		
Wholesaler		
Date	Model #	