

ANYSTREAM RAIN™



S-2559



S-2659



S-2555

Showerheads

GENERAL SPECIFICATION

Flow control device reduces flow to 2.5 gpm/9.46 lpm maximum to meet existing ANSI A112.18.1 standard. 1/2" NPT inlet. Brass ball swivel joint connection.

S-2559

Anystream Rain™ downpour showerhead only. Polished chrome plated 7½" diameter solid brass downpour showerhead. 96 spray streams positioned for a full-body coverage rain shower. Brass ball swivel joint connection.

S-2659

Anystream Rain™ downpour rain showerhead. With "S" shaped shower arm. Polished chrome plated 7½" diameter solid brass downpour showerhead. 96 spray streams positioned for a full-body coverage rain shower.

S-2555

Polished chrome plated Downpour Rain S-2555 Showerhead. Polish chrome finish. 108 individual water streams for full deluge shower. A 5" diameter solid brass showerhead, with a 10" pivoting extension arm that allow for various positioning of the showerhead. The pivoting extension arm will allow for a 20" range of motion.

OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> BN	Brushed nickel finish (S-2559, S-2659 only)
<input type="checkbox"/> ORB	Oil rubbed bronze finish (S-2559, S-2659 only)
<input type="checkbox"/> PB	Polished brass finish (S-2559, S-2659 only)

This space for Architect/Engineer approval.

