


Hydraulic Royal[®] Model Flushometer



Description

Exposed Hydraulically Operated Water Closet Flushometer, for floor mounted or wall hung top spud bowls.

Flush Cycle

☐ Model 910 Water Saver (3.5 gpf/13.2 Lpf)
☐ Model 910-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Closet Flushometer with the following features:

- Dual Filtered By-pass
- ADA Compliant Non-Hold-Open feature type Actuator (specify Actuator type listed below)
- 1" I.P.S. Screwdriver Bak-Chek™ Angle Stop
- Free Spinning Vandal Resistant Stop Cap
- Adjustable Tailpiece
- High Back Pressure Vacuum Breaker Flush Connection with One-piece Bottom Hex Coupling Nut
- Spud Coupling and Flange for 1½" Top Spud
- Sweat Solder Adapter with Cover Tube and Cast Set Screw Wall Flange
- Diaphragm, Stop Seat and Vacuum Breaker to be molded from PERMEX™ rubber compound for Chloramine resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037, ANSI/ASME 112.19.6, and Military Specification V-29193.

Actuator Types: (please check one)

☐ FW	Fixture Wall Actuator (HY-33-A) (rear access required)
☐ MP	Metal Partition Actuator (HY-49-A)
SW	Side Wall Mounted Actuator (HY-72-A)
MBFW	Metal Button Fixture Wall Actuator (HY-100-A) (rear access required)
☐ MBPM	Metal Button Panel Mount (HY-108-A)

See Actuator Specification pages in this section for details on Actuators.

Variations

variatio	113
□ ТР	Trap Primer
☐ YG	Extended Bumper on Angle Stop (for seat with cover)
☐ YO	Bumper on Angle Stop (for open front seat without cover)

See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.

Hydraulic Flushometer can also be provided in Regal® Models. All rough-in dimensions remain the same. Consult the factory.







This space for Architect/Engineer approval

The information contained in this document is subject to change without notice.

Made in the U.S.A.



SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL 60131 PHONE: 1-800 982-5839 • FAX: 1-800 447-8329 • http://www.sloanvalve.com