# TOTO<sub>®</sub>

# **TMU1LN Series**

## Non-Hold Open High-Efficiency Urinal Flushometer Valve - 0.5 gpf

#### **FEATURES**

- Manual operated, non-hold open, urinal flushometer valve complete with 3/4" angle stop and 3/4" or 1-1/4" vacuum breaker set
- Piston valve action with 0.5 gpf
- Left/right rough-in

#### **MODELS**

- TMU1LN#CP Valve only, Right/Left hand rough
- TMU1LN12#CP (3/4" Vacuum breaker)
  Right/Left hand rough
  Complete set supplied with:
  Vacuum breaker & angle stop set VB9CP-12
  - 3/4" Angle stop 10077t4
  - 3/4" Vacuum breaker 10075t2
  - Spud nut & escutcheon 71051Nt5
  - Sweat solder kit TH559EDVSJ1
- TMU1LN22#CP (1-1/4" Vacuum breaker)
  Right/Left hand rough
  Complete set supplied with:
  Vacuum breaker & angle stop set VB9CP-22
  - 3/4" Angle stop 10077t4
  - 1-1/4" Vacuum breaker 10075t5
  - Spud nut & escutcheon 71051Nt7
  - Sweat solder kit TH559EDVSJ1
- Optional Part: Z-4000-J - Adapter for ground joint angle stops

#### COLORS/FINISHES

#CP Polished Chrome

### CODES/STANDARDS

- Meets or exceeds ASSE 1037, CSA B125.3
- Certifications: IAPMO(cUPC), ASSE, State of Massachusetts, City of Los Angeles, and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- ADA compliant







#### PRODUCT SPECIFICATION

TOTO® Model No.

Manual type urinal flushometer valve, non-hold-open piston type with, self-cleaning debris screen and precise flushing capability. Low consumption water of 0.5 gpf/1.9 lpf model. Accessories to include angle stop with check valve, vacuum breaker. Sweat solder kit, spud nut and escutcheon.

### Non-Hold Open Urinal Flushometer Valve - 0.5 gpf

### **SPECIFICATIONS**

Three Year Warranty Warranty Material Bronze casting with

polished chrome finish

Water Supply 3/4" NPT

Fixture type Low consumption urinal

0.5 gpf / 1.9 lpf flushometer type

Supply water pressure 15 psi - 100 psi\*

These specifications are subject to change without notice.

\*Water pressures over 80 psi are not recommended for most plumbing fixtures. Check your local plumbing code for details.



