



model 8122HWC

Barrier-Free Emergency Equipment

FEATURES & BENEFITS

VALVES

Valve is designed so the full flow of water remains on with the simple tug of the triangular pull rod. Unit also comes equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

PULL ROD

Barrier-free designed unit comes equipped with 56" long pull rod to accommodate wheel chair access.

QUALITY CONTROL

Valve assembly is pre-built for reduced installation time and an added peace of mind for the installer.

SAFETY

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

SHOWER HEAD

AXION MSR[®] ABS plastic drench shower head uses a hydrodynamic design to give equal distribution of water throughout the entire footprint of flow.

OPTIONS

- Alarm: Model 9001, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a double pole, double throw flow switch.
- Alarm: Model 9001EXP 120 VAC Class 1, Division 2, Groups B, C, and D emergency alarm system. Buzzer and flashing light are activated by an 1-1/4" double pole, double throw flow switch.
- Shower Test Kit: Model 9010 shower test kit includes holding rod, upper corrosion-resistant ring to encircle the shower head, and Tyvek waterproof tunnel shaped tube to guide the water column to container or drain.
- Tempered Water Blending Systems: Model TWBS.SH, prepackaged, fully engineered and tested system for mixing hot and cold water to provide tempered water up to 40 gpm for emergency showers and eyewashes (Pat.# 5,350,112).

To see all options for this model, visit www.hawesco.com



SPECIFICATIONS

Model 8122HWC horizontally mounted barrier-free drench shower shall include the AXION MSR[™] hydrodynamic designed ABS plastic showerhead with self-regulating 20 gpm flow control, chrome-plated brass stay-open ball valve equipped with a stainless steel ball and stem, 56" stainless steel pull rod with triangular handle for wheel chair accessibility, universal sign, and 1" IPS supply.

APPLICATIONS

Where the body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching and cleansing of the body shall be provided within the work area for immediate emergency use. Emergency deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8122HWC is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.