

Location:




# SYMMONS® Degas™

## Shower System S-5401

### Specification Submittal



#### Feature Highlights

- Symmons Shower System with lever handle
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Secondary integral volume control handle
- Showerhead #402SH2, three mode, 7-1/2 inch diameter
- Showerhead arm and flange
- Standard flow rate is 2.5 gpm (9.5 L/min)  
*Optional lower flow rate restrictor available* 
- Polished chrome finish

#### Model Numbers

- S-5401  
Shower System with Symmons Temptrol® mixing valve  
p/n S-4001-BODY
- S-5401-TRM  
Trim only, mixing valve ordered separately
- S-4001-BODY  
Symmons Temptrol® mixing valve without trim
- S-4001-X-BODY  
Symmons Temptrol® mixing valve without trim.  
Valve includes integral service stops to allow water  
shut-off for service

#### Finish Options / Modifications

*Append appropriate -suffix to model number*



- STN Satin Nickel
- ORB Oil Rubbed Bronze
- Polished Chrome (standard finish)

#### Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

#### Options / Modifications

*Append appropriate -suffix to model number*

- IPS 1/2 inch female IPS connections on  
Symmons Temptrol® mixing valve  
*(not available with -X integral service stops)*
- X Integral service stops included with  
Temptrol® mixing valve to allow water  
shut-off for service, p/n S-4001-X-BODY  
*(option only applies when ordering S-5401)*
- REV Reverse coring in valve for back to back  
installations; hot on right, cold on left,  
*(only available with -X integral service stops)*
- L/HD Showerhead not included  
*(includes showerhead arm and flange only)*
-  -2.0 2.0 (7.6 L/min) flow rate restrictor
-  -1.5 1.5 (5.7 L/min) flow rate restrictor

#### Warranty

- Limited Lifetime - to the original end purchaser in  
consumer installations
- 5 years - for commercial installations

# Dimensions Degas Shower System, S-5401

