



model 8123HPCP

Laboratory Units

FEATURES & BENEFITS

CONSTRUCTION

1" Schedule 40 polished chrome-plated brass pipe and fittings provide an added corrosion resistance in a long lasting product.

FLOW CONTROLS

High polished stainless steel showerhead with integral 20 gpm flow control provide an added protection in highly corrosive environments and an optimal water flow for the irrigation process.

VALVES

Brass stay-open ball valve is designed so the full flow of water remains on with the simple tug of a pull down lever. Unit also comes equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

PULL ROD

28" stainless steel triangular pull rod provides a reachable height for users while maintaining its durable design.

MOUNTING

Designed for horizontal installation, this drench shower is mounted sturdily from any wall.

QUALITY CONTROL

High polished stainless steel head design resists dust build up as well as the potential outgas of products in highly corrosive environments.

SAFETY

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.



SPECIFICATIONS

Model 8123HPCP drench shower shall include a high-polished stainless steel 10-1/2" showerhead with integral self-regulating 20 gpm flow control, polished chrome-plated brass stay-open ball valve equipped with a stainless steel ball and stem, stainless steel pull rod with triangular handle, universal sign, and 1" IPS supply.

APPLICATIONS

Where the body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching and cleansing of the body shall be provided within the work area for immediate emergency use. Emergency deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8123HPCP is certified by CSA to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.

OPTIONS

- Alarm: Model 9001, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a double pole, double throw flow switch.
- Alarm: Model 9001EXP 120 VAC Class 1, Division 2, Groups B, C, and D emergency alarm system. Buzzer and flashing light are activated by an 1-1/4" double pole, double throw flow switch.
- Shower Test Kit: Model 9010 shower test kit includes holding rod, upper corrosion-resistant ring to encircle the shower head, and Tyvek waterproof tunnel shaped tube to guide the water column to container or drain.
- Privacy Curtain: Model 9037, privacy curtain designed to be used on horizontal emergency drench shower or combination emergency drench shower and eyewash units.

To see all options for this model, visit www.hawesco.com