

COMMERCIAL

S-2288-AF



Commercial Brass Showerheads

GENERAL SPECIFICATION

Polished chrome plated. Water conserving pressure compensating Autoflo® device reduces flow to a maximum of 2.5 gpm/9.46 lpm, to meet existing ANSI A112.18.1 Standard. Vandal-resistant standard. 1/2" NPT inlet.

S-2288-AF

Watersaver showerhead. Brass shank. Brass adjustable spray face. Brass ball swivel joint.

S-2460-AF

Solid brass Adjusta-Spray wall mounted showerhead. 2" face. 60 spray channels at three different angles to allow a full coverage shower. Drilled for, but less mounting bolts.

S-2280-AF

Anystream wall mounted showerhead. Rigid brass ball. Spray adjusting T-handle 2-1/2" face. 4 Lexan® deposit resisting plungers with 32 spray channels. Drilled for, but less mounting bolts.

S-2285-AF

Watersaver showerhead. Rigid brass head. Adjustable spray. Drilled for, but less mounting bolts.

S-2460-AF



S-2280-AF



OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> S-2280AFAPBJE15	Low flow head (1.5 gpm, 5.7 lpm) (S-2280 only)
<input type="checkbox"/> AP	Anchor plate assembly with mounting screws (not S-2288-AF)
<input type="checkbox"/> BJ	Ball joint (S-2280, S-2285 only)
<input type="checkbox"/> BPT	1/2" British pipe thread inlet (S-2288-AF only)
<input type="checkbox"/> 2	S-2252-AF Anystream showerhead (S-2280 only)

S-2285-AF



This space for Architect/Engineer approval. _____

