

T&S BRASS AND BRONZE WORKS, INC. 2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690



Model No.

EC-3102-HG

Sheet: 1 of

REG. #A2601 Item No.

		ISO #9001	ROM NO.
Travelers Rest, SC: 800-476-4103 Simi Valley, CA: 800	0-423-0150 Fax: 864-834-3518	www.tsbrass.com	
This Space for Architect/Engineer Approval			
Job NameDate			ChekPoint*
Model SpecifiedQuantity			
Customer/Wholesaler	ADA Compliant		
Contractor			
Architect/Engineer		4 3/16" x 2" De	
Sen	Waterpr w/ Interi AC or D [610mm] sor Cable	nal Flow Contro C operated w/ -Generator is N	odule Box (Blue) ol Setting Switches, (4) AA Batteries
DECK	[1031111]		•
1/2" NPSM x 1/4" NPSM 18" [457mm] Long Flexible St. Steel Hose (1)	2 1/4" Max. [57mm] Ø1" [25mi Deck Hole	m]	√ 1/8" [3mm] Pin installed for Anti-rotation feature. Remove pin if desired. (See Mounting Hole Detail)
Hydro-Generaror Power Supply. No AA Batteries or AC Adapter Needed to Supply Power to Faucet.	Also Includes Optiona 100-135 VAC Adapte w/ 144" [3658mm] Lo Power Cord. (Remove Rubber Plug on Module and Cable to Connect)	r ng gs	Mounting Hole Detail Ø1" [25mm]
Temperature Mixing Valve w/ Integral Check Valves NOTE: Supply Stops by Others	Furnished w/ (2) 3/8" Compression x 1 18" [457mm] Flex. St. Supply Hose		(25mm) Ø 5/32" [4mm]
Product Specifications: Chrome Plated Brass			cked Approved
Hole Deck Mt. Spout w/ VR Aerator, A w/ Internal Flow Cont. Setting Switche			MH JHB
Mixing Valve w/ Integral Check Valves 18" Long Hot & Cold Supply Stop Flex	s, Hydro-Generator,	Scale: 1:8	Date: 10/16/09



T&S BRASS AND BRONZE WORKS, INC.

2 Saddleback Cove / P.O. Box 1088 Travelers Rest, SC 29690




Model No.

EC-3102-HG

6. #A2601 Item No.

Travelers Rest, SC: 800-476-4103 Simi Valley, CA: 800-423-0150 Fax: 864-834-3518 www.tsbrass.com

ITEM NO.	SALES NO.	DESCRIPTION
1	016355-45	Aerator w/ Key, Vandal Resistant, 2.2 GPM, 13/16-27 Male
2	017195-45	Angled Sensor w/ Cable
3	016297-45	Inlet Hose, Faucet, 1/2" NPSM-F x 1/4" NPSM-F
4	016647-45	ChekPoint Module (Blue)
5	5EF-0002	A/C Transformer
6	5EF-0006	Mechanical Mixing Valve
7	5EF-0005	Supply Hose, 9/16-24 Female x 1/2" NPSM
8	Q015425-45	Vandal Resistant Key
9	EC-HYDROGEN	Hydro-generator and Swivel Coupling
10	017506-45	1/2 NPSM Swivel Coupling



Label for Flow Control Switch Settings is located on Inside of Back Cover.

Flow Control Switches are located inside Module Housing in Black Box next to Battery Compartment.
*Switches are set to DEFAULT position: Auto Time Out = 10 seconds
Shut Off Delay = 1 second

Remove (4) screws and back cover to access switches.

*Available Water Flow Control Selections:

(6) Auto Time Out Selections - 10 sec, 25 sec, 45 sec, 60 sec, 3 min, 20 min

(6) Shut Off Delay Selections - 1 sec, 2 sec, 3 sec, 4 sec, 5 sec, 6 sec

Product Specifications: Chrome Plated Brass Electronic Faucet: Sgl. Hole Deck Mt. Spout w/ VR Aerator, AC/DC Cont. Module w/ Internal Flow Cont. Setting Switches, Temperature Cont. Mixing Valve w/ Integral Check Valves, Hydro-Generator, 18" Long Hot & Cold Supply Stop Flexible Connector Hoses

Drawn	Checked	Approved
DHL	DMH	JHB
Scale:		Date:
1:8		10/16/09