

## ANYSTREAM®



**S-2251**



**S-2252**



**S-2252-1776**



**S-2253-AF**

## Showerheads GENERAL SPECIFICATION

Water conserving pressure compensating AUTOFLO® device reduces flow to 2.5 GPM/9.46LPM maximum, to meet existing ANSI A112.18.1M Standard. ½" NPT inlet.

**S-2251**

Polished chrome plated Anystream® showerhead. Brass ball swivel joint. Brass shank. Spray adjusting handle. 3-1/2" face. 8 Lexan deposit resisting plungers with 64 spray channels.

**S-2252-AF**

Polished chrome plated ANYSTREAM showerhead. Brass ball swivel joint. Brass shank. Spray adjusting T-handle. 2-3/4" face. 6 Lexan deposit resisting plungers with 48 spray channels.

**S-2252-1776**

Rough nickel plated Anystream® Liberty Bell showerhead. Brass ball swivel joint. Brass shank. Spray adjusting handle. 2-3/4" face. 6 Lexan deposit resisting plungers with 48 spray channels.

**S-2253-AF**

Polished chrome plated Anystream® showerhead. Brass ball swivel joint. Chrome plated shank. Spray adjusting T-handle. 2-1/4" face. 4 Lexan deposit resisting plungers with 32 spray channels.

### OPTIONS

SUFFIX	DESCRIPTION
<input type="checkbox"/> BB	Bright brass finish (S-2253-AF only)
<input type="checkbox"/> BP	Blister pack packaging (S-2253-AF only)
<input type="checkbox"/> BPT	1/2" British pipe thread inlet (not S-2252-1776)
<input type="checkbox"/> ORB	Oil rubbed bronze (SD-02 and S-2251 only)
<input type="checkbox"/> PN	Polished nickel finish (S-2251 only)
<input type="checkbox"/> PVD	Polished brass finish (S-2251 only)
<input type="checkbox"/> SC	Brushed chrome finish (S-2251 only)
<input type="checkbox"/> SN	Brushed nickel finish (S-2251 only)
<input type="checkbox"/> WGTPCBP	White with polished chrome trim (S-2253-AF)

\_\_\_\_\_  
 This space for Architect/Engineer approval.

