

# 7000B

Eye/Face Washes



## FEATURES & BENEFITS

### Flow Control

Omni-Flo wrap-around eye/face wash assembly with built-in 6.25 gpm self-regulating flow control offers a superior coverage area and assures efficient water flow.

### Valve

Valve is designed to make the flushing of fluid occur with the push of a stainless steel flag, and is equipped with a stainless steel ball and stem to provide added protection against corrosion and breakage.

### Quality Control

Eye/face wash and valve assembly is pre-built and fully water/pressure tested to ensure no leaks and proper function which ultimately reduces installation time and gives the end contractor an added peace of mind. Unit also ships with pre-assembled 16 gauge Type 304 Stainless Steel wall bracket to assist with the installation process.

### Safety

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

### Protection

Chrome-plated brass in-line 50 x 50 mesh water strainer prevents debris from reaching the eyewash so the unit stays functioning at its best. Strainer is easily serviceable. Yellow plastic dust cover protects the Omni-Flo eye/face wash from debris further optimizing operation.



## SPECIFICATIONS

Model 7000B wall-mounted eye/face wash shall include Omni-Flo wrap around eye/face wash with integral yellow plastic dust cover, chrome-plated brass stay-open ball valve equipped with stainless steel ball and stem, chrome-plated brass in-line 50 x 50 mesh water strainer, and Omni-Flo foam filter. Unit shall also include 16 gauge Type 304 Stainless Steel wall bracket, universal sign, 1/2" IPS inlet, and 1-1/4" IPS outlet.

## OPTIONS

- ☐ Tempered Water Blending Valves: Model 9201, thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- ☐ Tempered Water Blending Valves: Model 9201EF, thermostatic mixing valve that mixes hot and cold water to supply tempered water to eyewashes requiring flow up to 7 gpm @ 30 psi.
- ☐ Foot Treadle: Model SP220W wall mounted foot control assembly, including powder-coated aluminum treadle and wall bracket for hands free activation of eyewash.
- ☐ Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" double pole, double throw flow switch.

## APPLICATIONS

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing and cleansing of the eyes and face be provided within the work area for immediate emergency use. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 7000B is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.