2-3/4" [70mm]

DIA. FLANGE

FITTING NO. **CHICAGO** 2100 SOUTH CLEARWATER DRIVE 536 DES PLAINES, ILLINOIS 60018-5999 **FAUCETS** SUBMITTED MODEL NO. a Geberit company JOB NAME ITEM NO. NOTE: ALL DOTTED LINE PIPING SUBMITTED AS SHOWN IS 3/8" IPS UNLESS OTHERWISE SPECIFIED AND SUPPLIED BY OTHERS SUBMITTED AS NOTED SEE ATTACHED FOR FOR PROPER HEIGHT SUBMITTED MODIFICATION 2-1/4 OF INSTALLATION SEE [57mm] LOCAL PLUMBING CODE 3/8" NPT FEMALE 1-1/2 REQUIREMENT INLET AND OUTLET [38mm] (4) 5/16" [8mm] DIA. HOLES 6" [152mm] 5-5/8 MINIMUM [143mm] [102mm] **FLEXIBLE** UNION RECOMMENDED 11-1/2 (BY OTHERS) [292mm] 9-3/4 13-3/4 [349mm] [248mm] 2-1/2 **ADJUSTABLE** [64mm] 2-3/4" DIA. 23" MIN. 3/8" NPT BUSHED TO [70mm] 14-1/2" [584mm] **FEMALE** 3/8" NPT (TYP) INLET [368mm] HOLD DOWN RING 1-1/8" 1-3/8 1/2" NPT FEMALE 1-3/16 [29mm] DIA. INLET AND OUTLET [30mm] 9-3/4" [35mm] [248mm] (TYP) 1-1/4 1-1/8 [32mm] [29mm] 2-1/8" 3-3/8 1/2" NPT FEMALE [86mm] [54mm] THREAD INLETS

TECHNICAL DATA DATE: 02-25-05 - 537 HOSE REEL ASSEMBLY BY: JAR - 80 SELF CLOSING SPRAY VALVE - RETRACTABLE 35'X3/8" I.D. RUBBER HOSE 536 - 893 ATMOSPHERIC VACUUM BREAKER CHK'D: - 633 INDEXED CROSS-HANDLE - 1771C LOOSE KEY CHECK VALVES - SLOW COMPRESSION CARTRIDGES - E7FC PRESSURE RELIEF BLEEDER OUTLET - 767VOC CONCEALED TWO-VALVE FITTING APP'D: - ASME A112.18.1M COMPLIANT - 770 SHUT OFF VALVE - CSA B125 COMPLIANT - FINISH: NO FINISH REV: C

3"±1/2"

[76mm±13mm]

1-1/8

[29mm]

1-3/16"

[30mm]

1/2" NPT FEMALE

INLET AND OUTLET

8 "

3/4" GPM [2.8 L/min.] BLEEDER

TO REDUCE BACK PRESSURE ON

VACUUM BREAKER WHEN SHUT-OFF

AND/OR MIXING VALVE IS OPEN AND PRE-RINSE VALVE IS CLOSED.

[203mm]