

8901B

Emergency Equipment Parts and Accessories



FEATURES & BENEFITS

Safety

8" x 10-3/4" universal emergency sign make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

Eye/Face wash Heads

Green ABS Feather-Flo® head provides multiple soft-and-steady flowing streams of water for a maximum coverage area of the eyes, face, and body. Further equipped with integral flip top dust cover that automatically releases with the flow of water, unit stays protected from debris up until the last second before use.

Flow Control

Rubber 6.25 gpm flow insert automatically controls the water flow rate to produce a full continuous flow of water for the irrigation process.

Eye/Face wash Valve

Valve is designed so full continuous flow occurs with the simple squeeze of a lever providing an easy start to the irrigation process.

Hose

The 8' swivel hose delivers a wide coverage area and is pressure rated at 250 psi to further optimize durability.

Mounting

Wall-mounted design with wall hook allows for easy locating as well as a space efficient piece of emergency equipment.



SPECIFICATIONS

Model 8901B wall-mounted eye/face wash and body spray shall include a green Feather-Flo® ABS plastic eye/face wash head with integral flip-top dust cover, chrome plated brass stay-open squeeze lever valve with integral 4 gpm flow control, 8-foot 250 psi green rubber hose with chrome-plated swivel fitting at one end, wall-mounting bracket, universal sign, and 1/2" IPS inlet.

OPTIONS

- Tempered Water Blending Systems: Model TWBS.EW, prepackaged, fully engineered and tested hot and cold water blending system with fail-safe features to produce up to 5 gpm tempered water for eye/face washes (Pat.# 5,350,112).
- Tempered Water Blending Valves: Model 9201, thermostatic mixing valve that mixes hot and cold water for the tempering of eye/face wash units at a maximum flow rate of 20 gpm.
- Tempered Water Blending Valves: Model 9201EF, thermostatic mixing valve that mixes hot and cold water to supply tempered water to eyewashes requiring flow up to 7 gpm @ 30 psi.
- Alarm: Model 9001.5, 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by a 1/2" double pole, double throw flow switch.

To see all options for this model, visit www.hawasco.com.

APPLICATIONS

Perfect for the environment where safety is of the utmost importance and an extended coverage area may be needed. When installed properly, the functional constructed, wall mounted design of the 8901B is not only space efficient it meets the current ANSI standards of the Federal State Drinking Water Act.

Per ANSI, "Hand held drench hoses provide support for emergency shower and eyewash units, but shall not replace them."

