

ANYSTREAM 2000®

S-2005-HOTEL



S-2005-HB



S-2005-HS



GENERAL SPECIFICATION

Water conserving pressure compensating Autoflo® device reduces flow to 2.5 GPM/9.46LPM maximum, to meet existing ASME A112.18.1 standard. Brass threaded inlet with 1/2" NPSM inlet. There is also a dual action combination spray.

S-2005-HOTEL

Polished chrome plated Anystream S-2000® Showerhead. Spray adjusting T-handle. 2-1/2" face. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

S-2005-HB

Polished chrome plated Anystream S-2000® Showerhead. Spray adjusting T-handle. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

S-2005-HS

Polished chrome plated Anystream S-2000® Showerhead. Spray adjusting T-handle. 5 self-cleaning plunger nozzles resist scale build-up and provide 50 spray streams for a full body coverage pattern. Center core nozzles deliver 8 pulsating-massage jets.

OPTIONS

| SUFFIX | DESCRIPTION |
|----------------------------------|---|
| <input type="checkbox"/> BB | Bright brass (S-2005-HB only) |
| <input type="checkbox"/> BBHOTEL | Bright brass (S-2005-HOTEL only) |
| <input type="checkbox"/> BN | Brushed nickel finish (S-2005-HOTEL only) |
| <input type="checkbox"/> BP | Blister pack packaging (S-2005-HOTEL) |
| <input type="checkbox"/> SC | Satin chrome finish (S-2005-HB only) |
| <input type="checkbox"/> SN | Satin nickel finish (S-2005-HB only) |
| <input type="checkbox"/> WHT | White finish (S-2005-HB, S-2005-HS only) |

This space for Architect/Engineer approval.