



# AquaContour

Barrier Free, 14 Gage Stainless Steel, Bi-Level, Wall Mounted Water Cooler

## SUGGESTED SPECIFICATIONS

Model A152408B-FG is a wall mounted, vandal resistant bi-level pressure water cooler that shall deliver a minimum of **8.0 GPH** (30.3 LPH) of water at 50°F (10°C) cooled from 80°F (26.7°C) inlet water and 90°F (32.2°C) ambient. Unit shall be made from **14 gage, 304 stainless steel** with a brushed finish. Unit shall be activated by self-closing, front push buttons, by using less than 5 pounds of force, which activates internally mounted valves with adjustable stream regulators controlling the water flow. Evaporator shall be insulated tube on tank. Cooling system shall use R-134a refrigerant and be capillary tube controlled. An adjustable thermostat with an off position shall control the refrigeration system. Bubblers shall be polished chrome plated brass with non-squirt features and operate on water pressure range of 20-105 psig. Unit shall have uniquely designed, contoured bowls with P-traps integral to the unit. Unit shall adhere to ANSI A117.1 and Americans with Disabilities Act of 1990 frontal approach and protruding objects requirements, **Child ADA** parallel and frontal approach and ANSI/NSF 61, Section 9. Unit shall be listed by Underwriters Laboratories for both the US and Canada, compliant to the Air Conditioning and Refrigeration Institute Standard 1010.

**Stainless Steel Model:**  
A152408B-FG



## STANDARD FEATURES

- 14 gage, 304 stainless steel
- Both Child and Adult ADA Compliant (when properly installed)
- Polished chrome plated brass, anti-rotation non-squirt bubblers
- 100 mesh inlet strainer
- Vandal resistant screws
- Integral P-trap
- Mounting frame
- Back panel and louvered grille

Model Number	GPH*	Rated Watts	Full Load Amps	Approx. Shipping Weight
A152408B-FG	8.0	390	4.6	150 lbs.

\* GPH of 50°F water at 90°F ambient room temperature and 80°F inlet water temperature  
Compressor motor operates on 115 Volt / 60 Hz single phase.



Member of  
U.S. Green  
Building  
Council



Recyclable  
Product



Water  
Conserving  
Product

## OPTIONAL ACCESSORIES (additional costs)

- "F"** Flexible bubblers (Use model A152408F-FG)
- HP High polished stainless steel
- RBL Reverse bi-level
- "S"** Polished stainless steel, lead-free bubblers (Use model A152408S-FG)
- SK2 Skirt kit, 14 gage stainless steel, for upper unit
- SO Sensor operated
- WF1 1500 gallon capacity, NSF 42+53, 1 micron lead reduction filter
- 220V 220 volt / 50 Hz compressor (€€)
- "2"** Dark bronze finish (Use model A152208B-FG)
- "3"** Gold finish (high polished only) (Use model A152308B-FG)

Custom color finishes available upon request

Acorn Aqua™ assumes no responsibility for use of void or suspended data. © Copyright 2009 Acorn Aqua™, City of Industry, CA, A Division of Acorn Engineering Company. Please visit [www.acornaqua.com](http://www.acornaqua.com) for most current specifications.

Submittal # **A152408B-FG**  
[Sec. A] Rev. D 8/1/09

COMPLIES WITH  
**STANDARDS**



Test rating conditions are compliant with ARI 1010.



Member of Acorn  
Family of Companies


ACORN AQUA  
15125 Proctor Avenue  
City of Industry, CA  
91746 U.S.A.  
Phone 800-591-9360  
626-336-4561  
Fax 626-855-4894  
[www.acornaqua.com](http://www.acornaqua.com)



# TECHNICAL DIMENSIONS

All dimensions are nominal and subject to manufacturer's change without notice. Acorn Aqua™ assumes no responsibility for use of void or suspended data. © 2009 Acorn Aqua™, a Division of Acorn Engineering Company. Please visit [www.acornaqua.com](http://www.acornaqua.com) for most current specifications.

**Stainless Steel Model:**  
A152408B-FG



**GENERAL NOTES:**

1. ALL DIMENSIONS ARE IN INCHES [MM]
- \*2. DIMENSIONS SHOWN ARE FOR RECOMMENDED ADULT HEIGHT. ADJUST VERTICAL DIMENSIONS AS NECESSARY TO COMPLY WITH FEDERAL, STATE, & LOCAL CODES.
3. WATER LINES FROM CHILLER TO FOUNTAIN SHOULD BE COVERED WITH SPONGE RUBBER OR ICE WATER TYPE INSULATION OF ADEQUATE THICKNESS.

**AquaContour** Barrier Free, 14 Gage Stainless Steel,  
Bi-Level, Wall Mounted Water Cooler

Rough-in # **A152408B-FG** Rev. B 8/1/09

**Five Year Limited Warranty-** (Continental United States and Canada Only) The following components are warranted for five years: Compressor, Condenser Coil and Refrigeration Coil. The following components shall only be warranted for a period of one year: Evaporator Can Assembly, Thermostat, Fan Motor, Cartridge, Push Buttons, Compressor Starting Relay/Overload/Capacitor and Activation Linkage. Other parts are warranted for one (1) year from date of installation.  
**Limited Export Warranty-** One (1) year on parts only.

SELECTION SUMMARY & APPROVAL FOR MANUFACTURING

Company \_\_\_\_\_

Model Number & Options \_\_\_\_\_ Quantity \_\_\_\_\_

Contact \_\_\_\_\_ Title \_\_\_\_\_

Signature (Approval for Manufacturing) \_\_\_\_\_

Date \_\_\_\_\_



**800-591-9360**  
626-336-4561  
[www.acornaqua.com](http://www.acornaqua.com)