

200-AGN8AE3-317XKCP

Deck Mounted 8" Widespread Faucet with Spray

PRODUCT TYPE

Deck mounted 8" widespread faucet with spray

FEATURES & SPECIFICATIONS

- Polished chrome plated finish
- Solid brass body construction
- 8" Rigid valve body centers
- 8" C-C Rigid/Swing field convertible gooseneck spout, catalog #GN8A
- 2.2 GPM (8.3 L/min) pressure compensating aerator outlet, catalog #E3
- 4" Wristblade metal handles with eight point broach and secured color coded index buttons, catalog #317
- Ceramic disc cartridge with tapered square broach to facilitate handle removal, catalog #377-XKLH and #377-XKRRH
- Spray with 4' vinyl hose
- Internal diverter
- 1/2" NPSM supply inlets with coupling nuts for 3/8" or 1/2" flexible risers
- Mounting hardware included
- Internal diverter with anti-syphon

PERFORMANCE SPECIFICATION

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140° F

WARRANTY

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

COMPLIANT TO

- | | |
|-------------------|------------|
| • ASME A112.18.1M | • CSA B125 |
| • NSF 61, Sec. 9 | • ADA |



200-AGN8AE3-317XKCP


Deck Mounted 8" Widespread Faucet with Spray

**CHICAGO
FAUCETS**

a Geberit company

Architect/Engineer Specification

Chicago Faucets No. 200-AGN8AE3-317XKCP, Polished chrome plated solid brass body and spout. 8" C-C rigid/swing field convertible gooseneck spout. 2.2 GPM pressure compensating aerator outlet. 4" wristblade handles with eight point tapered broach and secured color coded index buttons. Ceramic disc cartridge with square tapered broach feature to help facilitate handle removal. Spray with 4' vinyl hose, 8" rigid valve body centers, spray diverter and 1/2" NPSM threaded inlets with coupling nuts for connection to 3/8" or 1/2" standard flexible risers. Mounting hardware included. This product meets ADA requirements and is tested and certified to industry standards: ASME A112.18.1, NSF 61, Sec. 9 and CSA B125.



OPERATION AND MAINTENANCE

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning this product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at www.chicagofaucets.com.

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.



2100 South Clearwater Drive
Des Plaines, IL 60018
P: 847/803-5000
F: 847/803-5454
Technical: 800/TEC-TRUE
www.chicagofaucets.com