ACCESSORIES AND PARTS 81-LCP



Product Type

Water Conserving 45° Angle Pre-Rinse Valve

Features & Specifications

- 3/4" 14 UNS Male Thread Inlet
- 1.42 GPM @ 60 PSI 110°F Water
- Angled Rubber Bound Spray Head
- Heat Resistant Actuator Handle with Hold Down Ring
- Compatible with Fisher and T&S Hoses
- Replaced 90-ANGABCP

Codes & Standards

• ASME A112.18.1/CSA B125.1

Job Name	_
Item Number	-
Section/Tag	_
Model Specified	-
Architect	_
Engineer	_
Contractor	_
[] Submitted as Shown [] Submitted with Variations	
Date	








Architect/Engineer Specification

Chicago Faucets No. 81-LCP polished chrome plated solid brass construction. Integral inlet shank(s). 3/4" - 14 UNS male thread inlet. 1.42 GPM @ 60 psi - 110°f water. Angled rubber bound spray head. Heat resistant actuator handle with hold down ring. Compatible with fisher and t&s hoses. Replaced 90-angabcp. Mounting hardware included.



Operation and Maintenance

Installation should be in accordance with local plumbing codes. Flush all pipes thoroughly before installation. After installation, remove spout outlet or flow control and flush faucet thoroughly to clear any debris. Care should be taken when cleaning the product. Do not use abrasive cleaners, chemicals or solvents as they can result in surface damage. Use mild soap and warm water for cleaning and protecting the life of Chicago Faucet products. For specific operation and maintenance refer to the installation instructions and repair parts documents that are located at www.chicagofaucets.com.

Chicago Faucets, member of the Geberit Group, is the leading brand of commercial faucets and fittings in the United States, offering a complete range of products for schools, laboratories, hospitals, office buildings, food service, airports and sport facilities. Call 1.800.TECTRUE or 1.847.803.5000 Option 1 for installation or other technical assistance.



2100 South Clearwater Drive Des Plaines, IL P: 847/803-5000 F: 847/803-5454 Technical: 800/TEC-TRUE