

### Pre-Rinse Fittings

#### Product Type

Deck Mounted Single Hole Deck Mounted Pre-Rinse Fitting

#### Features & Specifications

- Single Hole
  - 1.0 GPM @ 60 PSI Spray Valve
  - 2-3/8" Lever Handle
  - Quatum Compression Operating Cartridge
  - 3 1/2" Inlet Tee Connection with 1/4" NPT Check Stop
- Tailpieces
- 23" Riser with Spring Guide
  - 44" Flexible Stainless Steel Hose with Insulated Handle
  - Pipe Strap and Hook Assembly
  - ECAST® design provides durable brass construction with total lead content equal to or less than 0.25% by weighted average
  - CFNow! Item Ships in 5 Days

#### Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

#### Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

#### Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- California Health and Safety Code 116875 (AB1953-2006)
- Vermont Bill S.152
- NSF/ANSI 372 Low Lead Content

Job Name \_\_\_\_\_

Item Number \_\_\_\_\_

Section/Tag \_\_\_\_\_

Model Specified \_\_\_\_\_

Architect \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor \_\_\_\_\_

Submitted as Shown       Submitted with Variations

Date \_\_\_\_\_



ECAST products are intended for installation where state laws and local codes mandate lead content levels or in any location where lead content is a concern.

