



# model 8300FP

Combination Units

## FEATURES & BENEFITS

### CONSTRUCTION

1-1/4" Schedule 40 hot-dipped galvanized steel pipe and fittings along with powder-coated cast-iron 9" diameter floor flange provide corrosion resistance in a long lasting product.

### FLOW CONTROLS

Green ABS designed plastic showerhead and anti-surge Soft-Flo eyewash heads equipped with integral 20 gpm flow shower control and built in 1.2 gpm (2) flow eyewash control allow both parts of the emergency equipment to be safely used simultaneously. Flow controls provide the optimal water flow for an ideal coverage area.

### VALVES

Self-draining eyewash and shower valves are designed to make the flushing of fluid remains occur with the simple push of either of the individual push plates. Special self-draining feature prevents the unit from freezing.

### DUST COVERS

Green polyethylene plastic dust covers that release with water pressure keep the unit protected from debris up until the last second before use further optimizing operation.

### STRAINERS/FILTERS/MISC.

Large zinc-plated push plates with graphics are clearly labeled on how to operate the equipment so no time is wasted when an emergency arises.

### QUALITY CONTROL

Entire unit is pre-built and fully water and pressure tested to ensure no leaks and proper function for reduced installation time and an added peace of mind.

### SAFETY

8" x 10-3/4" universal combination emergency sign and 21" self-adhesive high visibility stripe in Safety Green and bright yellow make the unit easily detected in an emergency. Test card to record weekly checks helps maintain the unit's best working quality.

## OPTIONS

- Universal Sign: Model 9020 green and yellow ABS plastic 3-sided high visibility sign.
- Shower Head: Model 8127FC, corrosion-resistant 10-1/2" stainless steel showerhead with integral 20 gpm flow control.

To see all options for this model, visit [www.hawesco.com](http://www.hawesco.com)



## SPECIFICATIONS

Model 8300FP freeze resistant combination shower and eyewash shall include a green ABS plastic 10-5/8" showerhead with integral self-regulating 20 gpm flow control, stainless steel 11" round bowl, stainless steel eyewash yoke assembly with Soft-Flo ABS plastic eyewash anti-surge heads with integral flow controls and dust covers, two self-draining bury valves with available frost-line depths of 24" and 42" depths, two large zinc-plated steel push plates with universal graphics, powder-coated cast-iron 9" diameter floor flange, universal sign, 3/4" IPS and 1-1/4" IPS inlet, and 1-1/4" IPS outlet.

## APPLICATIONS

Where the eyes or body of any person may be exposed to injurious or corrosive materials, suitable facilities for quick drenching or flushing of the eyes and body shall be provided within the work area for immediate emergency use. Emergency eyewash facilities and deluge showers shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach.

Model 8300FP is certified by CSA & IAPMO to meet the ANSI Z358.1-2009 Standard for Emergency Eyewash and Shower Equipment.