

ANYSTREAM® Eco

Low Flow Showerheads

GENERAL SPECIFICATION

Full-body, infinitely adjustable spray streams. Anystream plunger nozzle system delivers great spray intensity at any water pressure. Large operating handle for precise control and easy spray selection. Meets ANSI A112.18.1. 1/2" NPT inlet. Recommended for U.S. Green Building Council LEED Rating System Project Certification.

□ **S-2253-E15**

4-jet showerhead. 32 sprays. 2-1/4" face diameter. Pressure-compensating Autoflo device limits flow to 1.5 gpm/5.6 lpm

□ **S-2253-E175**

4-jet showerhead. 32 sprays. 2-1/4" face diameter. Pressure-compensating Autoflo device limits flow to 1.75 gpm/6.6 lpm

□ **S-2253-E20**

4-jet showerhead. 32 sprays. 2-1/4" face diameter. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm.

□ **S-2252-E20**

6-jet showerhead. 48 sprays. 2-3/4" face diameter. Solid brass large-body construction. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm

□ **S-2005-H-E2**

5-jet showerhead. 50 sprays. 3-1/4" face. Adjustable spray with massage. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm.

□ **S-2005-HB-E2**

5-jet showerhead. 50 sprays. 4-1/4" face. Adjustable spray with massage. Pressure-compensating Autoflo device limits flow to 2.0 gpm/7.6 lpm.

S-2253-E15
S-2253-E175
S-2253-E20

S-2252-E20

S-2005-H-E2

S-2005-HB-E2

This space for Architect/Engineer approval.

