

Location:



SYMMONS® Elm™
Shower Valve System S-5500
Specification Submittal



Feature Highlights

- Symmons Shower Valve System with lever handle
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Screwless escutcheon
- Secondary integral volume control handle
- Polished chrome finish

Model Numbers

- S-5500
Shower Valve System with Symmons Temptrol® mixing valve p/n S-4001-BODY
- S-5500-TRM
Trim only, mixing valve ordered separately
- S-4001-BODY
Symmons Temptrol® mixing valve without trim
- S-4001-X-BODY
Symmons Temptrol® mixing valve without trim. Valve includes integral service stops to allow water shut-off for service

Finish Options / Modifications

Append appropriate -suffix to model number

- STN Satin Nickel
- SBZ Seasoned Bronze
- Polished Chrome (standard finish)

Options / Modifications

Append appropriate -suffix to model number

- IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve (not available with -X integral service stops)
- X Integral service stops included with Temptrol mixing valve to allow water shut-off for service, p/n S-4001-X-BODY (option only applies when ordering S-5500)
- CHKS Check Stops: Temptrol® mixing valve includes integral check stops (Requires integral service stops, suffix -X. Used in installations where a positive shut-off device is used downstream of mixing valve.)
- REV Reverse core: Temptrol® mixing valve with reverse core. (Requires integral service stops, suffix -X. Used in back-to-back system installations. HOT on the right, COLD on the left)


Standards / Certifications

ASME A112.18.1-2005 / CSA B125.1-05
Americans with Disabilities Act (ADA) compliant

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

Dimensions Elm Shower Valve System, S-5500



Note: Dimensions subject to change without notice