


## LABORATORY FAUCET - DOUBLE

Z826T4

TA			
IAI			
1//	$\smile$		

## Engineering Specifications: Zurn AquaSpec® Z826T4

Polished chrome-plated double laboratory faucet with integral shank, quarter turn ceramic disc cartridges and a 4-1/2" [114mm] centerline rigid gooseneck spout with vacuum breaker. Unit is furnished with a 2.2 GPM [8.3 L] pressure compensating aerator (complying with ANSI A112.18.1 Standard for flow), 4" [102mm] vandal-resistant color-coded metal wrist blade handles, mounting hardware and stainless steel flex connection hoses.



Note: All dimensions are for reference only. Do not use for pre-plumbing.

## **OPTIONAL ACCESSORIES**

Suffix	Description
AR	Anti-Rotation Pins
CST	Copper Supply Tubes
FC G	2.0 GPM [7.6 L] Laminar Flow Control in Base of Spout
G	1-1/4" [32mm] Grid Strainer Drain
GH	1-1/4" [32mm] Offset Handicap Grid Strainer
HCT	Hot/Cold Text Indexes
LP	Low Profile
MY	Mixing Yoke Assembly Instead of Copper Supplies
MYCS	Mixing Yolk with Check Stop
PT	1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend
6M	Male Serrated Nozzle Outlet
7M	1.0 GPM [3.8 L] Pressure Compensating Male Spray Outlet
16M	1.0 GPM [3.8 L] Vandal Resistant Pressure Compensating Male Spray Outlet
17M	1.5 GPM [5.7 L] Vandal Resistant Pressure Compensating Male Aerator
18M	1.5 GPM [5.7 L] Vandal Resistant Pressure Compensating Male Laminar Flow

ZURN INDUSTRIES, INC. ♦ COMMERCIAL BRASS OPERATION ♦ 2640 SOUTH WORK STREET ♦ FALCONER NY 14733 Phone: 1-716-665-1132 ♦ Fax: 1-716-665-1135 ♦ World Wide Web: www.zurn.com

In Canada: ZURN INDUSTRIES LIMITED ♦ 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2 ♦ Phone: 905/405-8272 Fax: 905/405-1292

Rev. D

Dwg. No. 65724